# **Architectural**

# **ACCESS DOOR**

The Babcock-Davis Architectural Access Door is built with the architect in mind. Constructed with an industry-standard steel door, the updated design further improves on strength and aesthetics.

## **FEATURES**

**ANTI-FLEX FRAME** Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.

**PAINLESS INSTALLATION** When mounting screws are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.

**OPTIONAL STAINLESS STEEL** The spot free design on the face of the door gives an aesthetically pleasing appearance.



#### **DETAILS**

### DOOR

- BNT/BNW: 16 gauge Steel
- BNP: 14 gauge Steel
- 16 gauge Type 304 Stainless Steel

#### **FRAME**

- 16 gauge Steel
- 16 gauge Type 304 Stainless Steel

#### SI7F

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

**INSTALLATION** Ceiling or Wall

FLANGE 1 inch Exposed, Drywall Bead or Plaster Bead

**HINGE** Concealed Spring Button

PAN DEPTH 1/2 inch

**FINISH** White Powder Coat (Steel) or #4 Satin (Stainless Steel)

#### **MATERIALS**







#4 Satin Stainless Steel

#### **FLANGES**



1 inch Flange



Drywall Bead



Plaster Bead

#### **LATCHES**



Screwdriver Cam Latch



Key Operated Cam Lock



Mortise Lock Prep



Knurled Knob

#### **ORDER GUIDE**

BASE	FLANGE	LATCH	WIDTH	Х	X LENGTH		OPTIONS	
BN				x				
	T 1 inch Flange			Standard Sizes (W x L)			Galvannealed	
	<b>W</b> Drywall Bead	Latch	6" x 6" 8" x 8"	16" x 20'		D14	14 gauge Steel Door	
	P Plaster Bead	L Key operated Cam Lock	10" x 10" 12" x 12"	18" x 24'		G	Gasketing	
		M Mortise Lock	12" x 18"	20 x 30 22" x 22'		L	Louvered Door	
		(1-1/8") Prep	12" x 24" 14" x 14"	22" x 30' 24" x 24'		М	Masonry Anchors	
		N Knurled Knob	16" x 16"	24" x 30'		S	Type 304 Stainless Steel	

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.